



Contribution ID: 54

Type: **not specified**

Design and fabrication of EXCALIBUR detector modules

Friday, 6 July 2012 09:50 (25 minutes)

The EXCALIBUR detector is a small-pixel photon counting area detector developed by the Diamond Light Source and the Science and Technology Facility Council in the UK for coherent X-ray diffraction. EXCALIBUR is based on the 55 micron pixel size read-out ASIC developed by the MEDIPIX3 collaboration. This talk describes the geometry of EXCALIBUR modules consisting of 16 MEDIPIX3 ASICs bump-bonded to a large silicon sensor die. The design of the hybrid carrier board and flexi-rigid circuits interfacing the hybrid pixel detector to FPGA boards will be presented as well as the strategy for controlling the temperature of the module. A description of module fabrication and quality control procedures at every step of the fabrication process will be provided. X-ray images obtained with an EXCALIBUR detector module will be presented together with the acquisition set-up developed for the transfer of 3M-pixel images produced by the final 3-module detector assembly at a frame rate of 100 frames per second in continuous mode and 1000 frames per second in burst mode.

Primary author: Dr MARCHAL, Julien (Diamond Light Source)

Presenter: Dr MARCHAL, Julien (Diamond Light Source)

Session Classification: Direct detection area detectors for storage rings I

Track Classification: Direct detection area detectors for storage rings