



# Series Measurements of the SLS2.0 Longitudinal Gradient Bends Magnets

## Challenges and Results

- G. Montenero, M. Aiba, C. Calzolaio, K. Dreyer, P. Lerch, and S. Sanfilippo
- 23rd International Magnetic Measurement Workshop Location, 08 October 2024, Bad Zurzach, Switzerland.

# Summary

- The SLS2.0 Arc
- The Triplet's Magnets (The LGB)
- Measurements' Challenges & Requirements
- Measurement Procedures
- Series Measurements Results
- Conclusions

## ➤ The SLS2.0 Arc

➤ The Triplet's Magnets

➤ Measurements' Challenges & Requirements

➤ Measurement Procedures

➤ Series Measurements Results

➤ Conclusions

# The SLS2.0 Arc



- **SLS2.0 keeps the same footprint of SLS-> magnets density along the ring increases of a factor 3.8**
- An SLS2.0 arc is based on a multi-bend achromatic structure (7BA)->emittance reduction by a factor  $\sim 40$
- The multi-bend design is implemented through Longitudinal Gradient Bends magnets-> Triplets in the PSI jargon
- Each arc has 5 triplets installed

➤ The SLS2.0 Arc

➤ **The Triplet's Magnets**

➤ Measurements' Challenges & Requirements


➤ Measurement Procedures

➤ Series Measurements Results

➤ Conclusions

# Triplet's Permanent Magnets

Mechanical reference frame



- **BN and BS2**
- BN is a normal dipole (56)
- BS2 is a longitudinal gradient dipole (4)

- **VB and VBX**
- VB is a combined function: quadrupole+dipole (96)
- VBX is a combined function: quadrupole+ dipole (24)

Arc type	Triplet 1	Triplet 2	Triplet 3	Triplet 4	Triplet 5	Number of Arcs
1	VBX(I)-BN <sup>1</sup> -VB <sup>1</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>3</sup> -BN <sup>3</sup> -VBX(O)	8
2	VBX(I)-BN <sup>1</sup> -VB <sup>1</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>4</sup> -BS2-VB <sup>4</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>3</sup> -BN <sup>3</sup> -VBX(O)	4

- The SLS2.0 Arc
- The Triplet's Magnets
- **Measurements' Challenges & Requirements**
- Measurement Procedures
- Series Measurements Results
- Conclusions

# Measurements' Challenges

## ❖ Main Challenges

- Each individual magnet must be tuned according to the standalone requirements (see also C. Zoller talk)
- As an assembly an extra tuning step is needed to accommodate for cross-talk effects (see also R. Riccioli talk)
- **From beam dynamics:** the Triplet integral function must be tuned with an overall uncertainty of  $2 \cdot 10^{-3}$  (or 20 (u)) relative to the nominal design ( $1 \text{ (u)} = 10^{-3}$ )
- Specific tuning parameters depending on the triplet type
  - VB-> 4 sets of tuning parameters
  - VBX-> 2 sets of tuning parameters
  - BN-> 3 sets of tuning parameters
  - BS2-> 1 set of tuning parameters

(true also for other SLS2.0 magnets)

- Several measurements steps: time consuming

## ❖ Defining Requirements

- The cross-talk effect, due to extreme dense lattice, obliges to optimize a Triplet as a full assembly with neighbours (iterative process)
- From an optimized triplet the magnetic axis of the single magnets must be extracted
- Each single magnet must be simulated as a standalone entity
- From field maps, simulations of the measurement process are carried out to calculate the design parameters for the tuning and adjustment of magnets (field quality and integral quantities)
- Each single step needs careful revision to avoid pitfalls

# Measurements' Requirements (1)

## ❖ Systems Requirements

- VB(X): Rotating Coil (RC) and Moving (Stretched) Wire (MV\_W) systems
- BN(BS2): Moving (Stretched) Wire
- Assembled Triplet: Moving (Stretched) Wire
- Each of the above steps needs survey operations

- VB's axis: line parallel to the mechanical axis that minimizes the L2 distance with the particle trajectory inside the magnet


## ❖ Desing Parameters: standalone (field quality->see slides 14-17 )

Magnet name    fDipole (Tm)    fGradient (T)    x0 (mm)

VBX(I)	-0.15244	5.5740	-0.435	} 0.8 m
VB <sup>1</sup>	-0.15669	7.0332	1.080	
VB <sup>2</sup>	-0.15358	6.9398	1.261	
VB <sup>3</sup>	-0.15640	7.0011	1.025	
VB <sup>4</sup>	-0.15100	6.8722	1.413	} 1.5 m
VBX(O)	-0.15240	5.5726	-0.435	
BN <sup>1</sup>	-0.57086		0	
BN <sup>2</sup>	-0.57265		0	
BN <sup>3</sup>	-0.57149		0	
BS2	-0.57698		0	

## ❖ Desing Parameters: Triplets->Integrals for MV\_W meas. at Positions 1 to 3 over 1.5 m (slide 24)

Arc type	Triplet 1	Triplet 2	Triplet 3	Triplet 4	Triplet 5	Number of Arcs
1	VBX(I)-BN <sup>1</sup> -VB <sup>1</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>3</sup> -BN <sup>3</sup> -VBX(O)	8
2	VBX(I)-BN <sup>1</sup> -VB <sup>1</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>4</sup> -BS2-VB <sup>4</sup>	VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	VB <sup>3</sup> -BN <sup>3</sup> -VBX(O)	4



# Measurements' Requirements (2)


- RC Bench 2 (0.5 m): Tuning VB(X) magnets
- MV\_W Bench 1 (0.8 m): VB(X) axis measurements
- MV\_W Bench 2 (1.5 m): BN/BS2 and Triplet tuning

RC Bench 2




08.10.2024

MV\_W Bench 1




Paul Scherrer Institute PSI



MV\_W Bench 2

3 points plane  
■ adjustment



10


- The SLS2.0 Arc
- The Triplet's Magnets
- Measurements' Challenges & Requirements
- **Measurement Procedures**
- Series Measurements Results
- Conclusions

# Triplet Measurement Procedures


## TRIPLET ASSEMBLY PROCESS

- **Step 1: VB and VBX measured and tuned with Rotating Coil**
  - 2 Steps measurement
    - Reference position: Adjustment of field value
    - Flip position: evaluation of magnet roll
    - Fiducialization with hexagon arm: referencing magnetic axis 'estimation' to magnet fiducials
- **Step 1: BN and BS2 measured and tuned with Moving Wire**
  - Fiducialization of the mechanical axis on a reference granite table (AT960 Hexagon)
  - Alignment on measurement bench: transfer of axis for stages starting position definition (AT960 Hexagon)
  - Measurement: Adjustment of field value
- **Step 2: VB and VBX axis measurement with Moving Wire**
  - Fiducialization of magnet's fiducials on reference granite table (AT960 Hexagon)
  - Roll angle alignment on Moving Wire bench (AT960 Hexagon)
  - Transfer of magnetic axis from Rotating Coil for initial wire positioning
  - Measurement: magnetic axis search
  - Fiducialization with AT960 Hexagon: referencing magnetic axis to magnet fiducials
- **Step 3: Triplet measurement and adjustment with Moving Wire**
  - Assembly of the Triplet
  - Alignment of the 3 magnets by survey team using fiducialization data from Step 1 (BN,BS2) and Step 2 (AT960 Hexagon)
  - Cross check of alignment, AT960 Hexagon, and calculations of initial wire set of starting positions
  - Measurement and tuning
  - Fiducialization with AT960 Hexagon: referencing Triplet magnetic axis to the magnets' assembly fiducials
  - **Cross the fingers until first beam : )!**

Prototyping phase (COVID era....)




Series (intermediate steps not shown ...)




- The SLS2.0 Arc
- The Triplet's Magnets
- Measurements' Challenges & Requirements
- Measurement Procedures
- **Series Measurements Results: Rotating Coil -> VB and VBX**
- Conclusions


# RC measurement Results: VBX(I) and VB<sup>1</sup>




• Tuned Integral B2/R<sub>ref</sub> @ 8.8 mm




• Tuned Integral B1 @ 8.8 mm




• Normal harmonics vs Simulated one




• Skew harmonics vs Simulated one




• Tuned Integral B2/R<sub>ref</sub> @ 8.8 mm



• Tuned Integral B1 @ 8.8 mm




• Normal harmonics vs Simulated one




• Skew harmonics vs Simulated one


# RC measurement Results: $VB^2$ and $VB^4$




• Tuned Integral B2/ $R_{ref}$  @ 8.8 mm




• Tuned Integral B1 @ 8.8 mm




• Normal harmonics vs Simulated one




• Skew harmonics vs Simulated one




• Tuned Integral B2/ $R_{ref}$  @ 8.8 mm



• Tuned Integral B1 @ 8.8 mm




• Normal harmonics vs Simulated one




• Skew harmonics vs Simulated one


# RC measurement Results: VBX(I) and VB<sup>1</sup>




• Tuned Integral B2/R<sub>ref</sub> @ 8.8 mm




• Tuned Integral B1 @ 8.8 mm




• Normal harmonics vs Simulated one




• Skew harmonics vs Simulated one




• Tuned Integral B2/R<sub>ref</sub> @ 8.8 mm



• Tuned Integral B1 @ 8.8 mm





• Normal harmonics vs Simulated one





• Skew harmonics vs Simulated one



# RC measurement Results: MV\_W Correction(d=6.36mm)





- **VBX(I) gradient error MV\_W measurements**





- **VBX(I) dipole error**
- **Axis error**





- **VB1, VB2, VB3, VB4 gradient error MV\_W measurements**



- **VB1, VB2, VB3, VB4 dipole error**
- **Axis error**





- **VBX(O) gradient error MV\_W measurements**





- **VBX(O) dipole error**
- **Axis error**

- The SLS2.0 Arc
- The Triplet's Magnets
- Measurements' Challenges & Requirements
- Measurement Procedures
- **Series Measurements Results: Moving Wire-> BN, VB, and VBX**
- Conclusions



# Moving Wire (d=6.36mm) Measurement Results: BN



- **BN<sup>1</sup>**
  - Tuning process
  - Residual mismatch





- **BN<sup>2</sup>**
  - Tuning process
  - Residual mismatch




- **BN<sup>3</sup>**
  - Tuning process
  - Residual mismatch

# Moving Wire Measurement Results: VBX(I) and VB1





- Dipole on axis
- $d=6.36$  mm





- Correction from RC measurements

08.10.2024





- Gradient from Horizontal and vertical measurements
- On axis  $\rightarrow d=6.36$  mm




- Correction from RC measurements

Paul Scherrer Institute PSI




- Initial wire offset w.r.t. magnetic axis from RC axis transfer
- RC uncertainty below  $100 \mu\text{m}$
- Machine requirements  $30 \mu\text{m}$

# Moving Wire Measurement Results: VB2




- Dipole on axis
- $d=6.36$  mm





- Correction from RC measurements

08.10.2024




- Gradient from Horizontal and vertical measurements
- On axis ->  $d=6.36$  mm









- Correction from RC measurements

Paul Scherrer Institute PSI




- Initial wire offset w.r.t. magnetic axis from RC axis transfer
- RC uncertainty below 100  $\mu\text{m}$
- Machine requirements 30  $\mu\text{m}$



# Moving Wire Measurement Results: VB and VBX(O)



- Dipole on axis
- $d=6.36$  mm



- Gradient from Horizontal and vertical measurements
- On axis  $\rightarrow d=6.36$  mm



- Initial wire offset w.r.t. magnetic axis from RC axis transfer
- RC uncertainty below  $100 \mu\text{m}$
- Machine requirements  $30 \mu\text{m}$

- Correction from RC measurements

08.10.2024

- Correction from RC measurements

Paul Scherrer Institute PSI

- The SLS2.0 Arc
- The Triplet's Magnets
- Measurements' Challenges & Requirements
- Measurement Procedures
- **Series Measurements Results: Moving Wire-> Triplets**
- Conclusions


# Moving Wire Measurement: Triplets Tuning

	Pos.1			Pos.2			Pos.3		
Triplet Type	$\int G$ (T)	$\int B_1$ (Tm)	dx.1 (mm)	$\int G$ (T)	$\int B_1$ (Tm)	dx.2 (mm)	$\int G$ (T)	$\int B_1$ (Tm)	dx.3 (mm)
VBX(I)-BN <sup>1</sup> -VB <sup>1</sup>	14.002	-0.87687	-4.920	13.920	-0.80819	0	13.860	-0.78761	1.484
VB <sup>2</sup> -BN <sup>2</sup> -VB <sup>2</sup>	15.356	-0.87746	-4.914	14.839	-0.80328	0	14.617	-0.78088	1.524
VB <sup>3</sup> -BN <sup>3</sup> -VBX(O)	13.969	-0.87709	-4.921	13.884	-0.80857	0	13.824	-0.78804	1.484
VB <sup>4</sup> -BN <sup>4</sup> -VB <sup>4</sup>	15.282	-0.87619	-4.922	14.799	-0.80217	0	14.510	-0.77309	1.988




## Tuning Strategy

- A. Initial measurement set on the calculated 3 positions
- B. Differences from model assessed
- C. Tuning strategy
  - i. Adjust moderator plates VB(X) to minimize gradient difference
  - ii. Use wire offset on the 3 positions to accommodate dipole residual mismatch

Wire displacement  $d=3.5$  mm to minimize multipole effects



# Moving Wire Measurement Results: Triplets



- Triplets **VBX(I)-BN<sup>1</sup>-VB<sup>1</sup>**
- Residuals of integral dipole vs gradient

- Triplets **VB<sup>2</sup>-BN<sup>2</sup>-VB<sup>2</sup>**
- Residuals of integral dipole vs gradient

- Triplets **VB<sup>3</sup>-BN<sup>3</sup>-VB<sup>3</sup>XO**
- Residuals of integral dipole vs gradient

- ✓ During series, Triplets tuning process successful mainly on position 1 and 2
- ✓ At position 3 data have a higher spread
- ✓ Systematics are within specs

- The SLS2.0 Arc
- The Triplet's Magnets
- Measurements' Challenges & Requirements
- Measurement Procedures
- Series Measurements Results: Moving Wire-> Triplets
- **Conclusions**

# CONCLUSIONS

- A complex measurement procedure was devised and resulted effective
- A model-based Triplet tuning process gave good results
- Time schedule is going to be respected (3 triplets every two weeks since beginning of this year)
- Tomorrow Triplet 55 (hopefully) will be delivered out of 60
- It has been an incredible journey: Thanks to everybody has been involved