

The XENON1T light calibration system

Payam Pakarha



Joint PhD seminar
August 26-27, 2015
Paul Scherrer Institute
Switzerland



**University of
Zurich**^{UZH}




The XENON1T PMT calibration system

- Construction started 2013 at LNGS, Italy .
- Having completed : water tank, ReStox (storage and recovery), cryostat, cryogenic and purification systems.
- Currently commissioning with 500 kg of xenon.
- To do: TPC and PMT array installations, electronics and DAQ.





Dark matter detection with XENON1T

- Prompt scintillation (S1), $\lambda = 178 \text{ nm}$.
- Secondary scintillation (S2) by e^- drift drift from ionization and extraction in gas.
- Drift time (Z) and hit pattern(X,Y) allows position reconstruction (precision: 0.2 mm Z, 1.6 mm X,Y).
- S1/S2 ratio depends on dE/dX , allows nuclear/electronic recoil discrimination (>99% efficiency).




XENON1T photosensors

- 3" PMTs from Hamamatsu model R11410-21 on top (127) and bottom (121) arrays (average QE 36%).
- Reduced radioactivity in collaboration with company "arXiv:1503.07698 [astro-ph.IM]" .




top



bottom

PMT calibration setup, schematics






Optical fibers

Fiber type 1: Guides the light from LED to the feed-through. Plastic fiber 980 μm core + 1.2 mm black jacket to prevent ambient light input.

Fiber type 2: Transfers the light from feed-through to the TPC. Quartz fiber 660 μm core + 110 μm Polyamide coating for thermal protection.

Fiber type 3: 1 \rightarrow 7 splitting fiber assembly to split the light into the top and bottom PMT array. Made of 250 μm PMMA (Polymethyl methacrylate) to optimize the flexibility.



Light sources

Pulse generator: BNC model 505, 4 channels. Remotely controllable via RS-232 port.

Digital clock (trigger generator): External timer module (from either SC or DAQ) should be used.


LED box: BNC input for TTL pulses from pulse generator. SMA optical output to guide the LED light (470 nm).



LED calibration frame




4 channel pulse generator




LED box

Test setup at UZH


Test setup was successfully made using MarmotXL LXe facility at UZH. Single photo-electron spectrum from 5 PMTs inside LXe was observed using fiber-optic setup.



Schematics of the test setup using MarmotXL chamber






LED box and optical vacuum feed-through



SPE spectrum from the test PMTs.


Installation

- Installation of the quartz fibers inside umbilical pipe (June 2014).
- Installation of the quartz fibers extension through the cryogenic line into the porcupine (January 2015).
- **To do:** Installation of PMMA fibers inside the TPC.
- **To do:** Installation of the plastic fibers and the LED frame inside DAQ room.




Light emission simulations [A. Kish]


- 4×6 light emitting fibers are distributed through the top and bottom PMT arrays.
- MC simulation with GEANT4 was used to estimate light collection efficiency on individual PMTs for different geometrical configuration of fiber placements.




Software Map, Light Points
Configuration 2: 1-to-6 splitting



PMT calibration software : work in progress ...




Raw data processing:
*Baseline subtraction
*pulse finding
*integration algorithm




SPE spectrum
and fitting

PMT calibration database



Monitoring plots :
Gains, noise rates, DC
rates and ...



Summary and outlook

- Individual sections of the PMT calibration system of the XENON1T detector were developed, built and tested at UZH.
- A major part of the system, including quartz fibers inside the umbilical pipe and cryogenic line through the vacuum FTs, were installed at LNGS.
- Installation of the PMMA fibers inside the XENON1T TPC and the connections of the light sources to the vacuum FTs are to be performed by September-October 2015.
- Work in progress to develop the PMT calibration software of the XENON1T detector in order to precisely measure PMT gains and other characteristics and regularly monitor their stability.

Any Questions?