

COMET

mu-e conversion search experiment at J-PARC

Satoshi MIHARA

KEK/J-PARC/Sokendai

Outline

- Introduction
 - Muon particle physics & mu-e conversion
- COMET experiment at J-PARC
 - Status of the experiment
 - Plan of the experiment
- Summary




COMET Cyclotron
at PSI


Muon particle physics & mu-e conversion

Muon Particle Physics

- Muon in the Standard Model
 - Precise measurement of muon properties
 - Establishment of SM
- Indication of BSM related to muon?
 - muon $g-2$, B leptonic decay ...




Branching Ratio UL




Bernstein & Cooper

Year

mu-e Conversion



$$\mathcal{L} = \frac{1}{1 + \kappa} \frac{m_\mu}{\Lambda^2} \bar{\mu}_R \sigma^{\mu\nu} e_L F_{\mu\nu} + \frac{\kappa}{1 + \kappa} \frac{1}{\Lambda^2} (\bar{\mu}_L \gamma^\mu e_L) (\bar{q}_L \gamma_\mu q_L)$$



Muon Decay In Orbit


nuclear muon capture



μ -e conversion



MEG 2016
 4.2×10^{-13}



Andre de Gouvea, W. Molzon, Project-X WS (2008)

Experimental Techniques

• Process : $\mu^- + (A,Z) \rightarrow e^- + (A,Z)$

• A single mono-energetic electron

• $E_{\mu e} \sim m_{\mu} - B_{\mu} : 105 \text{ MeV for Al}$

• Delayed : $\sim 1 \mu\text{S}$

• No accidental backgrounds

• Physics backgrounds

• Muon Decay in Orbit (DIO)


• $E_e > 102.5 \text{ MeV (BR: } 10^{-14} \text{)}$

• $E_e > 103.5 \text{ MeV (BR: } 10^{-16} \text{)}$

• Beam Pion Capture



• $\pi^- + (A,Z) \rightarrow (A,Z-1)^* \rightarrow \gamma + (A,Z-1)$
 $\gamma \rightarrow e^+ e^-$

$$R_{\text{ext}} = \frac{\text{number of proton between pulses}}{\text{number of proton in a pulse}}$$




Muon Decay In Orbit
nuclear muon capture

SINDRUM II




Electron Energy



Selection of the Target Material

- DIO E_{endpoing} extends to the $E_{\mu-e}$
 - Recoil energy
 - Muon binding energy
- Select the target material with high $E_{\mu-e}$ and avoid using the material with larger E_{endpoint} around the target
 - When the target is made of aluminium, we should avoid using materials from $Z=5$ to $Z=12$.
 - He ($Z=2$) is OK to use around the target
- Lifetime of muon in muonic atoms
 - Shorter in larger Z because of the larger nuclear muon capture rate





	Al	Ti
lifetime	864 ns	330 ns
time window	0.3	0.2
signal	1	1.5
net	0.3	0.3

Once the signal is observed...

Even without $\mu \rightarrow e \gamma$ signal !

On the model discriminating power
of $\mu \rightarrow e$ conversion in nuclei



Vector ²



Vector ¹

Dipole

Scalar

μ -e Conversion Search Experiments

- J-PARC
- DeeMe
- COMET Phase-I & II
- FNAL
- Mu2e (A. GAPONENKO's presentation)




$10^{-14} \sim 10^{-16}$ sensitivity

J-PARC

Japan Proton acceleration research complex

- Joint project between JAEA and KEK
- **New and accelerator research facility**, using MW-class high power proton beams at both 3 GeV and 30 GeV.
- Various secondary particle beams
 - neutrons, muons, kaons, neutrinos, etc. produced in proton-nucleus reactions
- Three major scientific goals using these secondary beams
 - Particle and Nuclear physics
 - Materials and life sciences
 - R&D for nuclear transformation (in Phase 2)
- The anticipated goal is 1 MW



J-PARC Facility (KEK/JAEA)

LINAC
400 MeV

Neutrino beam to Kamioka

Material and Life
Science Facility

Nuclear and Particle
Physics Exp. Hall

Rapid **C**ycle **S**ynchrotron
Energy : 3 GeV
Repetition : 25 Hz
Design Power : 1 MW

Main **R**ing
Max Energy : 30 GeV
Design Power for FX : 0.75 MW
Expected Power for SX : > 0.1 MW







COMET




COMET at J-PARC

- **Target S.E.S. 2.6×10^{-17}**
- Pulsed proton beam at J-PARC
 - Insert empty buckets for necessary pulse-pulse width
 - bunched-slow extraction
- pion production target in a solenoid magnet
- Muon transport & electron momentum analysis using C-shape solenoids
 - smaller detector hit rate
 - need compensating vertical field
- Tracker and calorimeter to measure electrons
- Recently staging plan showed up. The collaboration is making an effort to start physics DAQ as early as possible under this.



COMET Phase I & II

- Phase I
 - Beam background study
 - Achieve an intermediate sensitivity of $< 10^{-14}$
 - 8GeV, 3.2kW, 110 days of DAQ
- Phase II
 - 8GeV, 56kW, 1 year DAQ to achieve the COMET final goal of $< 10^{-16}$ sensitivity




Phase I
2013-2018
 Facility construction
2013-2019
 Magnet construction & installation
2018-2020
 Eng. run & Physics run
Phase II
 Eng. run in 2022(?)

Pion Capture


- Adiabatic transition of Muon beam

$$p_T \times R \propto \frac{p_T^2}{B} = \text{constant}$$


- As B decreases, p_T decreases and R increases
- more parallel beam at a cost of the increased beam size



Strong Magnetic field in high radiation environment



Aluminum stabilized SC
Collaborative R&D between
COMET & Mu2e





Muon Transport

- A center of helical trajectory of charged particles in a curved solenoidal field is drifted by


$$D[m] = \frac{1}{0.3 \times B[T]} \times \frac{s}{R} \times \frac{p_l^2 + \frac{1}{2}p_t^2}{p_l}$$

- This effect can be used for charge and momentum selection.
- This drift can be compensated by an auxiliary field parallel to the drift direction



$$\delta p / \delta x = 1 \text{ MeV}/c/\text{cm}$$


COMET Phase-I




COMET Phase-I Layout

COMET Status of COMET Experiment Facility


Switch Yard Beamline Elements



Beam line component installation in progress in SY since 2014



Beam transport line in HD hall



SC magnets

Hall construction



He compressor used for E36 will be reused for COMET



90 deg. Transport Solenoid installed in Spring 2015




COMET Hall ready in Spring 2015


Significant construction work **2016 Summer** to connect SY and Hall along the B-Line

COMET: Status of Detector Preparation

All geometry implemented in the full simulation: ICEDUST




Detector for physics measurement in Phase I




CDC : the main detector of COMET Phase-I Physics




Wire stringing completed in July 2016 at KEK



Analysis algorithm development in progress using simulation data.
ex) track finding in CyDET



Beam test @ PSI 2015







CDC Read Out Electronics RECBE production at IHEP

Trigger Hodoscope Counter
Scintillator + Cerenkov

CDC Construction

- COMET Phase-I Physics Main Detector
- Wire stringing completed in July 2016
- 1st cosmic-ray event observed in Sep. 2016




COMET: Detector Preparation Cont'd


Straw tracker (operational in vacuum) prototype




Detector for **beam BG measurement in Phase I** and **physics measurement in Phase II**



Ecal (LYSO) R&D using prototypes





Crystal quality test bench at JINR



↑ Wave form taken in the test
← Electron beam test at ELPH


Ecal Pile-up study using simulation data




Ecal PID performance evaluation at PSI 2015

Background Assessment

- Proton emission from muon captures
- No data available for Al
 - Si data only (near Al)
 - 15% proton emission / muon capture on ^{28}Si
 - $50\text{MeV}/c < p < 200\text{MeV}/c$
- Significant contribution to the detector hit rate
- AlCap experiment at PSI
 - **Joint effort between COMET/Mu2e**



Al



- 0.05 protons/ muon capture
- Tran Hoai Nam (Osaka Univ.) PhD

opportunities for cooperation with Mu2e



AlCap@PSI

Dec. 13

-  COMET
-  Mu2e

Background Phase-I


Type	Background	Estimated events
Physics	Muon decay in orbit	0.01
	Radiative muon capture	0.0019
	Neutron emission after muon capture	< 0.001
	Charged particle emission after muon capture	< 0.001
Prompt Beam	* Beam electrons	
	* Muon decay in flight	
	* Pion decay in flight	
	* Other beam particles	
	All (*) Combined	≤ 0.0038
	Radiative pion capture	0.0028
	Neutrons	$\sim 10^{-9}$
Delayed Beam	Beam electrons	~ 0
	Muon decay in flight	~ 0
	Pion decay in flight	~ 0
	Radiative pion capture	~ 0
	Anti-proton induced backgrounds	0.0012
Others	Cosmic rays [†]	< 0.01
Total		0.032

[†] This estimate is currently limited by computing resources.



Preparation for Phase-II

- 180 degree bend in the muon transport section
 - Better pi/mu separation and high-p particle rejection
- 180 degree bend in the electron spectrometer
 - Keep the detector occupancy rate reasonable even with higher primary beam power
 - Optimization of
 - muon stopping target disks
 - collimators in the electron spectrometer
- Detector R&D as a beam measurement detector in Phase-I


Phase-I



Phase-II




Principle of DeeMe





→ DeeMe

Principle of DeeMe



DeeMe at J-PARC

- mu-e conversion search at J-PARC with a S.E.S. of 10^{-14}
 - Primary proton beam from RCS
 - 3GeV, 1MW
 - Pion production target as a muon stopping target
 - Beam line as a spectrometer
 - Kicker magnets to remove prompt background
 - Multi-purpose beam line for DeeMe, HFS, g-2/EDM is under construction
 - Engineering run (DIO electron measurement) in JFY 2016



Summary

- muon as a tool to investigate BSM physics
- COMET searches for the mu-e conversion with a target sensitivity better than 10^{-16} at J-PARC
 - Staged approach: $< 10^{-14}$ in Phase I and $< 10^{-16}$ in Phase II
- Facility construction & detector preparation are in progress to start Phase-I in 2018-2019

Summary

- muon as a tool to investigate BSM physics
- COMET searches for the mu-e conversion with a target sensitivity better than 10^{-16} at J-PARC
- Staged approach: $< 10^{-14}$ in Phase I and $< 10^{-16}$ in Phase II
- Facility construction & detector preparation are in progress to start Phase-I in 2018-2019



presented at PSI2013



Bld. construction completed
in 2015 spring